



"CESSNA T207A (SOLOY) HIDROAVION PK4000 "CC-PAX"

A.- LIMITACIONES DE OPERACIÓN

1.- Limitaciones (KIAS)	
Va (4000 LBS)	
Vne	
Vfe 10° 10°- 30°	
Vx (SL)	
Vy (SL)	
Normal Climb Out	
V _{APP} (FLAPS DN)	
V _{PLANEEO} (4000 LBS)	
Max Cross Wind	

2.- Combustible (GAL)	
Tipo a Utilizar	
Capacidad Total	
Capacidad Usable	

3.- Pesos (LBS)	
Maximum TAKE-OFF	
Maximum LANDING	
Nose Baggage	
Floats Baggage	

4.- Starter Limitations	

B. - EMERGENCIES PROCEDURES

1. - ENGINE FAILURE DURING TAKEOFF RUN

Power Control

Control Wheel

Fuel Cutoff Control

Monitor

Battery Switch

FORCED LANDING

2. – EMERGENCY LANDING ON WATER WITHOUT ENGINE POWE

Airspeed

Propeller Control

Fuel Cutoff Control

Fuel Selector Valve

Flaps

Battery Switch

Water Rudders

Doors

Touchdown

Control Wheel

3. – EMERGENCY LANDING ON LAND WITHOUT ENGINE POWER

Airspeed

Propeller Control

Fuel Cutoff Control

Fuel Selector Valve

Flaps

Battery Switch

Water Rudders

Doors

Touchdown

Control Wheel

4. – EMERGENCY LANDING ON LAND WITH ENGINE POWER

Runway

Wing Flaps

Power Control

Airspeed

Battery Switch

Doors

Touchdown

Control Wheel

Fuel Cutoff Control

Fuel Selector Valve

5. - ENGINE FIRE IN WATER

Fuel Cutoff Control

Start Motor Switch

Fuel Selector Valve

Monitor

Fire Extinguisher

Engine Secure

Start Switch

Battery Switch

Exit Aircraft

6. – ENGINE FIRE IN FLIGHT

Fuel Cutoff Control

Propeller Control

Fuel Selector

Battery and Generator

Cabin Heat and Air

Airspeed

Forced Landing