



**DEPARTAMENTO “SEGURIDAD OPERACIONAL”  
SUBDEPARTAMENTO “LICENCIAS”  
SECCIÓN EVALUACIONES**

**“BEECHCRAFT BARÓN 58 Serie TH-1472 and After”**

**SEBASTIÁN DÍAZ SANTELICES**

**A.- Limitaciones de Operación**

**1.- Limitaciones (KIAS)**

Va	156
Vne	223
Vno	195
Vfe (Approch 15°)	152
Vle	152
Vmca	84
Vs	84
Vso	75
Vx	92
Vy	105
Vsse	88
Vxse	95
Vyse	100
Emergency Descent	152
Vbalked landing	95
Vapp (Flap DN)	122
Max Cross Wind	22

**2.- Combustible (U.S. GAL)**

Tipo a Utilizar	100/130
Capacidad Total	200
Combustible Usable	194
Presión de Combustible (GPH)	
Máxima	30
Mínima	3

**3.- Pesos (LBS)**

Máximo TAKE-OFF	5.500
Máximo Baggaje NOSE	300
Máximo Baggaje AFT + EXT	520

**4.- Motor (Potencia Máxima Continua)**

Limitaciones Operativas de Motor	
Razón HP o BHP	300
Máximas RPM	2.700
Temperatura Cabeza de Cilindros (°C)	
Máxima	238
Mínima	116
Temperatura de aceite (°C)	
Máxima	116
Mínima	24
Presión de aceite (PSI)	
Máxima	100
Mínima	25

**5.- Limites de Maniobras (Cat. Normal)**

Máxima Deslizada (Tiempo)	30''
Escarpados	156

## **B.- Emergencies Procedures**

### **1. ENGINE FAILURE DURING TAKEOFF**

Throttle	<b>CLOSED</b>
Braking	<b>MAXIMUM</b>

If insufficient runway remains for stopping:

Fuel Selector Valves	<b>OFF</b>
Battery	<b>OFF</b>
Generator / Alternator	<b>OFF</b>
Magneto / Start Switches	<b>OFF</b>

### **2. ENGINE FAILURE AFTER LIFT-OFF AND IN FLIGHT**

Landing Gear and Flaps	<b>UP</b>
Throttle (Inop. Engine)	<b>CLOSED</b>
Propeller (Inop. Engine)	<b>FEATHER</b>
Power (Oper. Engine)	<b>AS REQUIRED</b>
Airspeed	<b>MAINTAIN SPEED AT ENGINE FAILURE (100 KIAS MAX.) UNTIL OBSTACLES ARE CLEARED</b>

After positive control of the airplane is established:

Secure Inoperative Engine:

Mixture Control	<b>IDLE CUT-OFF</b>
Fuel Selector	<b>OFF</b>
Auxiliary Fuel Pump	<b>OFF</b>
Magneto/Start Switch	<b>OFF</b>
Alternator Switch	<b>OFF</b>
Cowl Flap	<b>CLOSED</b>

### 3. ENGINE FIRE ON THE GROUND

Mixture Controls	IDLE CUT-OFF
Continue	TO CRANK AFFECT ENGINE
Fuel Selector Valves	OFF
Battery and Generator/Alternator Switch	OFF
Extinguish	WITH FIRE EXTINGUISHER

### 4. ENGINE FIRE IN FLIGHT

Fuel Selector Valves	OFF
Mixture Controls	IDLE CUT-OFF
Propeller	FEATHERED
Aux Fuel Pump	OFF
Magneto/Start Switch	OFF
Alternator Switch	OFF

### 5. EMERGENCY DESCENT

Propellers	2.700 RPM
Throttles	CLOSED
Airspeed	152 KIAS
Landing Gear	DOWN
Flaps	APPROACH (15°)