



DEPARTAMENTO “SEGURIDAD OPERACIONAL”
SUBDEPARTAMENTO “LICENCIAS”
SECCIÓN EVALUACIONES

“CESSNA C-150L”

CLUB AÉREO DE PANGUIPULLI

A.- Limitaciones de Operación

1.- Limitaciones (Velocidades)

	MPH
Va	109
Vne	162
Vno	120
Vfe	100
Vs	55
Vso	48
Vx	70
Vy	76
Vr	55
Vapp (Flap DN)	60 – 70
Vplaneo	70 – 80
Max Cross Wind	15

2.- Combustible (U.S. GAL)

Tipo a Utilizar	100/130
Capacidad Total	26
Combustible Usable	22,5
Presión de Combustible (PSI)	
Mínima	Red line
Máxima	Red line

3.- Pesos (LBS)

Máximo TAKE-OFF	1.600
Máximo Equipaje	120

4.- Motor (Potencia Máxima Continua)

Limitaciones Operativas de Motor	
Razón HP o BHP	100
Máximas RPM	2.750
RPM estáticas	
Máximas	2.550
Mínimas	2.000
Temperatura de aceite (°F)	
Máxima	240
Mínima	Red line
Presión de aceite (PSI)	
Máxima	100
Mínima	10

5.- Límites de maniobras (Cat. Normal)

MANIOBRA	MPH
Spin (Flaps UP)	Show Deceleration
Escarpados	109
Ocho Flojo	109
Chandela	109

B.- Emergency Procedure

1.- ENGINE POWER LOSS DURING TAKEOFF (Not Airborne)

a.- Sufficient runway remaining:

Throttle	CLOSE IMMEDIATELY
Brakes	APPLY AS REQUIRED
Stop	STRAIGHT AHEAD

b.- Insufficient runway remaining:

Throttle	CLOSE IMMEDIATELY
Brakes	APPLY AS REQUIRED
Mixture	IDLE CUT-OFF
Fuel selector	OFF
Master switch	OFF
Magnetos	OFF
Directional Control	MAINTAIN - Maneuver to avoid obstacles.

2. - ENGINE POWER LOSS DURING TAKEOFF (if Airborne)

a.- Sufficient runway remaining:

Airspeed	MAINTAIN ABOVE STALL (70 MPH)
Directional control	MAINTAIN
Land	STRAIGHT AHEAD

b.- Insufficient runway remaining:

Airspeed	MAINTAIN ABOVE STALL (70 MPH)
Throttle	CLOSE
Mixture	IDLE CUT-OFF
Fuel selector	OFF
Flaps	AS REQUIRED
Master Switch	OFF
Magnetos	OFF
Directional Control	MAINTAIN – Make only shallow turns to avoid obstacles.

3. ENGINE FAILURE IN FLIGHT

Speed	70 MPH
Fuel selector	BOTH
Mixture	FULL RICH
Primer	SECURE
Magnetos	CHECK

4. ENGINE FIRE DURING START ON GROUND

Starter CONTINUE CRANKING

a.- If the start is successful:

Engine 1700 RPM FOR A FEW MINUTES

Before shutting it down to inspect damage.

b.- If engine start is unsuccessful:

Continue CRANKING FOR TWO OR THREE MINUTES
Throttle FULL OPEN

When ready to extinguish fire,

Starter RELEASE
Master switch OFF
Ignition switch OFF
Fuel shutoff valve OFF
Fire Damage INSPECT

5. ENGINE FIRE IN FLIGHT

Mixture control IDLE CUT-OFF
Fuel shutoff valve OFF
Master switch OFF
Establish a glide 100 MPH
Cabin heat control CLOSE
Select a field FORCED LANDING