



DEPARTAMENTO “SEGURIDAD OPERACIONAL”
 “SUBDEPARTAMENTO “LICENCIAS”

CESSNA SKYLANE C-182T NAVIII KAP140
CC-PNB

NOMBRE: _____ FIRMA: _____

FECHA : _____

A. OPERATING LIMITATIONS

1.- Limitations Speed (KIAS)

Va (3.100 lbs)	
Vne	
Vno	
Vfe (10°)	
Vs	
Vso	
Vx (Sea Level)	
Vy (Sea Level)	
Vr	
Vapp (Flaps Down)	
Vglide (3100 lbs)	
Max Cross Wind	

2.- Fuel (U.S. GAL)

Type to Use	
Total Capacity	
Usable Capacity	

2.1 Oil (U.S. Qts.)

Capacity	
----------	--

3.- Weight (LBS)

Maximum TAKE-OFF	
Maximum Baggage	

4.- Engine (Maximum Continuous Power)

Engine Operating Limitations	
Reason HP o BHP	
Maximum RPM	
Head Cylinder Temperature (°F)	
Minimum	
Maximum	
Oil Temperature (°F)	
Minimum	
Maximum	
Oil Pressure (PSI)	
Minimum	
Maximum	

5.- Maneuvering Limits (Normal Cat.)

MANEUVER	KIAS
Chandelle	
Lazy Eight	
Steep Turns	
Stall	

B. EMERGENCY PROCEDURES

1. ENGINE FAILURE DURING TAKEOFF ROLL

THROTTLE CONTROL _____

BRAKES _____

2. ENGINE FAILURE IMMEDIATELY AFTER TAKEOFF

AIRSPEED _____

3. ENGINE FAILURE DURING FLIGHT (Restart Procedures)

AIRSPEED _____

FUEL SELECTOR Valve _____

FUEL PUMP Switch _____

MIXTURE CONTROL _____

4. FIRE DURING START ON GROUND

MAGNETOS Switch _____

If Engine Starts:

POWER _____

ENGINE _____

If engine fails to start:

- THROTTLE CONTROL _____
- MIXTURE CONTROL _____
- MAGNETOS Switch _____
- FUEL SELECTOR Valve _____
- FUEL PUMP Switch _____
- MAGNETOS Switch _____
- STBY BATT Switch _____
- MASTER Switch (ALT and BAT) _____

5. ENGINE FIRE IN FLIGHT

- MIXTURE CONTROL _____
- FUEL SELECTOR VALVE _____
- FUEL PUMP Switch _____
- MASTER Switch (ALT and BAT) _____

6. ELECTRICAL FIRE IN FLIGHT

- STBY BATT Switch _____
- MASTER Switch (ALT and BAT) _____
- VENTS/CABIN AIR/HEAT _____
- FIRE EXTINGUISHER _____

7. CABIN FIRE

STBY BATT Switch

MASTER Switch (ALT and BAT)

VENTS/CABIN AIR/HEAT

FIRE EXTINGUISHER

8. H. WING FIRE

LAND and TAXI Light Switches

NAV Light Switch

STROBE Light Switch

PITOT HEAT Switch
