



DEPARTAMENTO “SEGURIDAD OPERACIONAL”
“SUBDEPARTAMENTO “LICENCIAS”

“CIRRUS SR22T”

“CC-AGO”

NOMBRE: _____ FIRMA: _____

FECHA : _____

A.- OPERATING LIMITATIONS

1.- Limitations (Speed) (KIAS)

Va	
Vne	
Vno	
Vfe 50%	
Vs	
Vso	
Vx (SL)	
Vy (SL)	
Vr	
Vapp (Flap DN)	
Vglide	
Max Cross Wind	

2.- Fuel (U.S. GAL)

Type to Use	
Total Capacity	
Usable Capacity	

3.- Weight (LBS)

Maximum TAKE-OFF	
Maximum Baggage	

4.- Engine (Maximum Continuous Power)

Engine Operating Limitations	
Reason HP o BHP	
Maximum RPM	
Cylinder Head Temperature (°F)	
Maximum	
Minumum	
Oil Temperature (°F)	
Maximum	
Minumum	
Oil Pressure (PSI)	
Maximum	
Minumum	

5.- Maneuvering Limits (Normal Cat.)

Spin (Flaps UP)	
Steep Turns	
Lazy Eight	
Chandelles	

B.- EMERGENCIES PROCEDURES

1.- ENGINE FAILURE DURING TAKEOFF RUN

Throttle Power Lever

Fuel Pump

Mixture

Fuel Selector

Ignition Switch

Bat – Alt – Master Switch

2.- ENGINE FAILURE IMMEDIATELY AFTER TAKEOFF

Airspeed

Mixture

Fuel Selector

Ignition Switch

Flaps

3.- ENGINE FAILURE DURING FLIGHT

Best Glide Speed

Fuel Selector

Ignition Switch

Fuel Pump

Power Lever

Mixture

4.- FIRE DURING START ON GROUND

Mixture

Fuel Pump

Fuel Selector

Power Lever

Power Starter

If flames persist, perform emergency engine shutdown on ground and
emergency ground egress checklists.

5.- ENGINE FIRE IN FLIGHT

Mixture

Fuel Pump

Fuel Selector

Airflow selector

Power Lever

Ignition Switch

Cabin Doors
